



RESIDUAL-CURRENT DEVICE COMPON.SUMMATION
CURR.TRANSF. W/O PICK-UP DELAY WINDOW 40MM
RTD.FAULT CURRENT 1A

General technical details:

Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750

K

Item designation / according to DIN EN 61346-2

K

Ambient temperature

- during operating

°C

-20 ... 70 ...

Mechanical design:

Diameter / of the feedthrough

mm

40

Conductor cross section that can be connected / of the terminal

mm²

2.5

Width

mm

100

Height

mm








65

Depth

mm

85

Certificates/approvals:

General Product Approval			Test Certificates	
 CSA	 GOST	 UL	Special Test Certificate	
Shipping Approval				other
 DNV	 GL	 LRS	 RMRS	Declaration of Conformity other
Further information:				
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/industrial-controls/catalogs				
Industry Mall (Online ordering system) http://www.siemens.com/industrial-controls/mall				
CAX-Online-Generator http://www.siemens.com/cax				
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3UL2201-3A/all				
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UL2201-3A				

last change:

Jan 21, 2013