



RESIDUAL-CURRENT DEVICE COMPON.SUMMATION
 CURR.TRANSF. W/O PICK-UP DELAY WINDOW 65MM
 RTD.FAULT CURRENT 1A

General technical details:

Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Item designation / according to DIN EN 61346-2		K
Ambient temperature		
• during operating	°C	-20 ... 70 ...

Mechanical design:

Diameter / of the feedthrough	mm	65
Conductor cross section that can be connected / of the terminal	mm ²	2.5
Width	mm	125
Height	mm	70
Depth	mm	110

Certificates/approvals:

General Product Approval

CSA



GOST



UL

Test Certificates[Special Test Certificate](#)**Shipping Approval**

DNV



GL



LRS



RMRS

other[Declaration of Conformity](#)[other](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3UL2202-3A/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UL2202-3A

last change:

Jan 21, 2013