



RESIDUAL-CURRENT DEVICE COMPON.SUMMATION  
 CURR.TRANSF. W/O PICK-UP DELAY WINDOW 120MM  
 RTD.FAULT CURRENT 1A

**General technical details:**

Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		K
Item designation / according to DIN EN 61346-2		K
Ambient temperature		
• during operating	°C	-20 ... 70 ...

**Mechanical design:**

Diameter / of the feedthrough	mm	120
Conductor cross section that can be connected / of the terminal	mm <sup>2</sup>	2.5
Width	mm	200
Height	mm	85
Depth	mm	200

**Certificates/approvals:**

**General Product Approval**

CSA



GOST



UL

**Test Certificates**[Special Test Certificate](#)**Shipping Approval**

DNV



GL



LRS



RMRS

**other**[Declaration of Conformity](#)[other](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/3UL2203-3A/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3UL2203-3A](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3UL2203-3A)

last change:

Jan 21, 2013