

Similar to image

CIRCUIT-BREAKER VL 160H HIGH BREAKING CAPACITY
 ICU=70KA / 415 V AC 3 POLE,
 LINE PROTECTION ELECTRONIC TRIP UNIT LCD ETU42,
 LSIG 3PHASES/4WIRES WITH PIGTAIL IN=100A,
 RATED CURRENT IR=40-100A,
 OVERLOAD ISD=1,5TO10XIR,
 II=11XIN SHORT-CIRCUIT WITHOUT AUXILIARY
 RELEASE

General technical data:		
Number of poles		3
Design of the overcurrent release		LCD ETU42
Acceptability for application		system/generator protection
Product component		No
<ul style="list-style-type: none"> • undervoltage release with leading contact 		
Protection class IP		IP20
Protective function of the overcurrent release		LSIG
Impulse voltage resistance / rated value	kV	8
Ambient temperature		
<ul style="list-style-type: none"> • during operating <ul style="list-style-type: none"> • minimum • maximum • during storage <ul style="list-style-type: none"> • minimum • maximum 	°C °C °C °C	-25 ... 70 -40 50
Main circuit:		
Insulation voltage / for AC / rated value	V	800
Operating frequency		
<ul style="list-style-type: none"> • 1 / rated value • 2 / rated value 	Hz Hz	50 60
Item designation		
<ul style="list-style-type: none"> • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2 		Q Q
Operating voltage		
<ul style="list-style-type: none"> • for main current circuit <ul style="list-style-type: none"> • at 50 Hz / for AC 		

<ul style="list-style-type: none"> • maximum 	V	690
<ul style="list-style-type: none"> • at 60 Hz / for AC 		
<ul style="list-style-type: none"> • maximum 	V	690
Continuous current / rated value	A	100
Derating temperature / for the rated value of the continuous current	°C	50
<ul style="list-style-type: none"> • acc. to UL 489 	°C	40

Short-circuit:

Adjustable response current		
<ul style="list-style-type: none"> • of the current-dependent overload release 		- ...
<ul style="list-style-type: none"> • initial value 		
<ul style="list-style-type: none"> • of the non-delayed short-circuit release 		- ...
<ul style="list-style-type: none"> • initial value 		
Breaking capacity limit short-circuit current (Icu) / at 415 V / rated value	kA	70


Installation/mounting/dimensions:

Type of mounting	fixed mounting
-------------------------	----------------

Connections:

Arrangement of electrical connectors / for main current circuit	front side
Design of the electrical connection / for main current circuit	box terminals

Certificates/approvals:

Test Certificates	Shipping Approval	other
Special Test Certificate		other
		Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL2710-2UM33-0A..all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL2710-2UM33-0A..

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013