SIEMENS

Product data sheet

3VL4731-3DK36-....

Similar to image

CIRCUIT-BREAKER VL 400L VERY HIGH BREAKING CAPACITY ICU=100KA / 415 V AC 3 POLE, STARTER COMBINATION PROTECTION OVERCURRENT RELEASE MAGNETIC IN=315A, RATED CURRENT II=2000-4000A, SHORT-CIRCUIT

General technical data:				
Number of poles		3		
Design of the overcurrent release		Μ		
Acceptability for application		Starter protection		
Product component				
 undervoltage release with leading contact 		No		
Protection class IP		IP20		
Protective function of the overcurrent release		1		
Impulse voltage resistance / rated value	kV	8		
Ambient temperature				
during operating				
• minimum	°C	-25		
• maximum	°C	70		
during storage				
• minimum	°C	-40		
• maximum	°C	50		

Main circuit:

Insulation voltage / for AC / rated value	V	800			
Operating frequency					
• 1 / rated value	Hz	50			
• 2 / rated value	Hz	60			
Item designation					
 according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 		Q			
according to DIN EN 61346-2		Q			
Operating voltage					
for main current circuit					
• at 50 Hz / for AC					
• maximum	V	690			

• at 60 Hz / for AC		
• maximum	V	690
Continuous current / rated value	А	315
Derating temperature / for the rated value of the continuous current	°C	50
• acc. to UL 489	°C	40

Sho	71 I	-	

Adjustable response current					
 of the current-dependent overload release 					
initial value					
 of the non-delayed short-circuit release 					
• initial value					
Breaking capacity limit short-circuit current (Icu) / at 415 V / rated value	kA	100			
Installation/mounting/dimensions:					
Type of mounting		fixed mounting			
Connections:					
Arrangement of electrical connectors / for main current circuit		front side			

Design of the electrical connection / for main current circuit

Certificates/approvals:

Oci fineates/appi					
General Product	Approval			EMC	Declaration of Conformity
	(SA)	GOST	<u>KTL</u>	С-ТІСК	EG-Konf.
Test Certificates					
Special Test Certificate	Type Test Certificates/Test				

screw-type terminals

Report

Shipping Approval

B U R E A U VER ITAS	GL	Llovďs Kegister Lrs	PRS	RINA	
other					
Confirmation	other	Environmental Confirmations			

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/3VL4731-3DK36-..../all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL4731-3DK36-....

CAx-Online-Generator http://www.siemens.com/cax

last change:

Feb 8, 2013