

Similar to image

CIRCUIT-BREAKER VL 630L VERY HIGH BREAKING CAPACITY ICU=100KA / 415 V AC 3 POLE, STARTER COMBINATION PROTECTION OVERCURRENT RELEASE MAGNETIC IN=315A, RATED CURRENT II=2000-4000A, SHORT CIRCUIT

General technical data:

Number of poles		3
Design of the overcurrent release		M
Acceptability for application		Starter protection
Product component • undervoltage release with leading contact		No
Protection class IP		IP20
Protective function of the overcurrent release		I
Impulse voltage resistance / rated value	kV	8
Ambient temperature • during operating • minimum • maximum • during storage • minimum • maximum	°C	-25 ... 70 -40 50

Main circuit:

Insulation voltage / for AC / rated value	V	800
Operating frequency • 1 / rated value • 2 / rated value	Hz	50 60
Item designation • according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 • according to DIN EN 61346-2		Q Q
Operating voltage • for main current circuit • at 50 Hz / for AC • maximum	V	690

<ul style="list-style-type: none"> • at 60 Hz / for AC • maximum 	V	690
Continuous current / rated value	A	315
Derating temperature / for the rated value of the continuous current	°C	50
<ul style="list-style-type: none"> • acc. to UL 489 	°C	40

Short-circuit:

Adjustable response current

- of the current-dependent overload release
 - initial value
- of the non-delayed short-circuit release
 - initial value

- ...
- ...

Breaking capacity limit short-circuit current (I_{cu}) / at 415 V / rated value

kA 100

Installation/mounting/dimensions:

Type of mounting

fixed mounting

Connections:

Arrangement of electrical connectors / for main current circuit

front side

Design of the electrical connection / for main current circuit

screw-type terminals

Certificates/approvals:

General Product Approval

EMC

Declaration of Conformity

Test Certificates



CCC



GOST



C-TICK



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



BUREAU VERITAS



GL



LRS



PRS



RINA

other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5731-3DK36-..../all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5731-3DK36-....

CAx-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013