

Similar to image

CIRCUIT-BREAKER VL 630L VERY HIGH BREAKING CAPACITY ICU=100KA / 415 V AC 3 POLE, LINE PROTECTION OVERCURRENT RELEASE TM, LI IN=400A, RATED CURRENT IR=315-400A, OVERLOAD II=2000-4000A, SHORT CIRCUIT

**General technical data:**

<b>Number of poles</b>		3
<b>Design of the overcurrent release</b>		TM
<b>Acceptability for application</b>		system protection
<b>Product component</b>		
<ul style="list-style-type: none"> <li>• undervoltage release with leading contact</li> </ul>		No
<b>Protection class IP</b>		IP20
<b>Protective function of the overcurrent release</b>		LI
<b>Impulse voltage resistance / rated value</b>	kV	8
<b>Ambient temperature</b>		
<ul style="list-style-type: none"> <li>• during operating</li> </ul>		
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	°C	-25 ...
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	°C	70
<ul style="list-style-type: none"> <li>• during storage</li> </ul>		
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	°C	-40
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	°C	50

**Main circuit:**

<b>Insulation voltage / for AC / rated value</b>	V	800
<b>Operating frequency</b>		
<ul style="list-style-type: none"> <li>• 1 / rated value</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>• 2 / rated value</li> </ul>	Hz	60
<b>Item designation</b>		
<ul style="list-style-type: none"> <li>• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> </ul>		Q
<ul style="list-style-type: none"> <li>• according to DIN EN 61346-2</li> </ul>		Q
<b>Operating voltage</b>		
<ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>		
<ul style="list-style-type: none"> <li>• at 50 Hz / for AC</li> </ul>		
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	V	690
<ul style="list-style-type: none"> <li>• at 60 Hz / for AC</li> </ul>		

• maximum	V	690
<b>Continuous current / rated value</b>	A	400
<b>Derating temperature / for the rated value of the continuous current</b>	°C	50
• acc. to UL 489	°C	40

#### Short-circuit:

##### Adjustable response current

- of the current-dependent overload release
  - initial value
- of the non-delayed short-circuit release
  - initial value

- ...

- ...

##### Breaking capacity limit short-circuit current (I<sub>cu</sub>) / at 415 V / rated value

kA 100

#### Installation/mounting/dimensions:

##### Type of mounting

fixed mounting

#### Connections:

##### Arrangement of electrical connectors / for main current circuit

front side

##### Design of the electrical connection / for main current circuit

screw-type terminals

#### Certificates/approvals:

##### General Product Approval

##### EMC

##### Declaration of Conformity

##### Test Certificates



CCC



GOST



C-TICK



EG-Konf.

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

##### Shipping Approval



GL



LRS



PRS



RINA

##### other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/3VL5740-3DC36-..../all>

---

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL5740-3DC36-....](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5740-3DC36-....)

---

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**last change:**

Feb 8, 2013