

Similar to image

CIRCUIT-BREAKER VL 630N STANDARD BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE, LINE PROTECTION ELECTRONIC TRIP UNIT ETU20, LSI IN=630A, RATED CURRENT IR=252-630A, OVERLOAD ISD=1,5TO9XIR, II=10XIN SHORT-CIRCUIT WITHOUT AUXILIARY RELEASE ETU COMMUNICATION-CAPABLE

### General technical data:

<b>Number of poles</b>		3
<b>Design of the overcurrent release</b>		ETU20
<b>Acceptability for application</b>		system/generator protection
<b>Product component</b>		No
<ul style="list-style-type: none"> <li>• undervoltage release with leading contact</li> </ul>		
<b>Protection class IP</b>		IP20
<b>Protective function of the overcurrent release</b>		LSI
<b>Impulse voltage resistance / rated value</b>	kV	8
<b>Ambient temperature</b>		
<ul style="list-style-type: none"> <li>• during operating</li> </ul>		
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• minimum</li> </ul> </li> </ul>	°C	-25 ...
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• maximum</li> </ul> </li> </ul>	°C	70
<ul style="list-style-type: none"> <li>• during storage</li> </ul>		
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• minimum</li> </ul> </li> </ul>	°C	-40
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• maximum</li> </ul> </li> </ul>	°C	50

### Main circuit:

<b>Insulation voltage / for AC / rated value</b>	V	800
<b>Operating frequency</b>		
<ul style="list-style-type: none"> <li>• 1 / rated value</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>• 2 / rated value</li> </ul>	Hz	60
<b>Item designation</b>		
<ul style="list-style-type: none"> <li>• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> </ul>		Q
<ul style="list-style-type: none"> <li>• according to DIN EN 61346-2</li> </ul>		Q
<b>Operating voltage</b>		
<ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>		
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• at 50 Hz / for AC</li> </ul> </li> </ul>		
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>• maximum</li> </ul> </li> </ul> </li> </ul>	V	690

<ul style="list-style-type: none"> <li>• at 60 Hz / for AC</li> <li>• maximum</li> </ul>	V	690
<b>Continuous current / rated value</b>	A	630
<b>Derating temperature / for the rated value of the continuous current</b>	°C	50
<ul style="list-style-type: none"> <li>• acc. to UL 489</li> </ul>	°C	40

#### Short-circuit:

##### Adjustable response current

- of the current-dependent overload release
  - initial value
- of the non-delayed short-circuit release
  - initial value

- ...

- ...

##### Breaking capacity limit short-circuit current (I<sub>cu</sub>) / at 415 V / rated value

kA

55

#### Installation/mounting/dimensions:

##### Type of mounting

fixed mounting

#### Connections:

##### Arrangement of electrical connectors / for main current circuit

front side

##### Design of the electrical connection / for main current circuit

screw-type terminals

#### Certificates/approvals:

##### General Product Approval



GOST

##### EMC



C-TICK

##### Declaration of Conformity



EG-Konf.

##### Test Certificates

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

##### Shipping Approval



GL



RINA

##### other

[Confirmation](#)

[other](#)

[Environmental Confirmations](#)

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5763-1ME36-0A..all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL5763-1ME36-0A..](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-1ME36-0A..)

**last change:**

Feb 8, 2013