

Similar to image

CIRCUIT-BREAKER VL 630H HIGH BREAKING CAPACITY  
 ICU=70KA / 415 V AC 3 POLE,  
 LINE PROTECTION ELECTRONIC TRIP UNIT LCD ETU42,  
 LSIG 3PHASES/3WIRES IN=630A,  
 RATED CURRENT IR=252-630A,  
 OVERLOAD ISD=1,5TO9XIR,  
 II=10XIN SHORT-CIRCUIT WITHOUT AUXILIARY  
 RELEASE

**General technical data:**

<b>Number of poles</b>		3
<b>Design of the overcurrent release</b>		LCD ETU42
<b>Acceptability for application</b>		system/generator protection
<b>Product component</b>		
<ul style="list-style-type: none"> <li>• undervoltage release with leading contact</li> </ul>		No
<b>Protection class IP</b>		IP20
<b>Protective function of the overcurrent release</b>		LSIG
<b>Impulse voltage resistance / rated value</b>	kV	8
<b>Ambient temperature</b>		
<ul style="list-style-type: none"> <li>• during operating</li> </ul>		
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	°C	-25 ...
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	°C	70
<ul style="list-style-type: none"> <li>• during storage</li> </ul>		
<ul style="list-style-type: none"> <li>• minimum</li> </ul>	°C	-40
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	°C	50

**Main circuit:**

<b>Insulation voltage / for AC / rated value</b>	V	800
<b>Operating frequency</b>		
<ul style="list-style-type: none"> <li>• 1 / rated value</li> </ul>	Hz	50
<ul style="list-style-type: none"> <li>• 2 / rated value</li> </ul>	Hz	60
<b>Item designation</b>		
<ul style="list-style-type: none"> <li>• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750</li> </ul>		Q
<ul style="list-style-type: none"> <li>• according to DIN EN 61346-2</li> </ul>		Q
<b>Operating voltage</b>		
<ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>		
<ul style="list-style-type: none"> <li>• at 50 Hz / for AC</li> </ul>		

<ul style="list-style-type: none"> <li>• maximum</li> </ul>	V	690
<ul style="list-style-type: none"> <li>• at 60 Hz / for AC</li> </ul>		
<ul style="list-style-type: none"> <li>• maximum</li> </ul>	V	690
<b>Continuous current / rated value</b>	A	630
<b>Derating temperature / for the rated value of the continuous current</b>	°C	50
<ul style="list-style-type: none"> <li>• acc. to UL 489</li> </ul>	°C	40

#### Short-circuit:

<b>Adjustable response current</b>		
<ul style="list-style-type: none"> <li>• of the current-dependent overload release</li> </ul>		- ...
<ul style="list-style-type: none"> <li>• initial value</li> </ul>		
<ul style="list-style-type: none"> <li>• of the non-delayed short-circuit release</li> </ul>		- ...
<ul style="list-style-type: none"> <li>• initial value</li> </ul>		
<b>Breaking capacity limit short-circuit current (I<sub>cu</sub>) / at 415 V / rated value</b>	kA	70


#### Installation/mounting/dimensions:

<b>Type of mounting</b>	fixed mounting
-------------------------	----------------

#### Connections:

<b>Arrangement of electrical connectors / for main current circuit</b>	front side
<b>Design of the electrical connection / for main current circuit</b>	screw-type terminals

#### Certificates/approvals:

Test Certificates	Shipping Approval	other
<a href="#">Special Test Certificate</a>		<a href="#">other</a>
		<a href="#">Environmental Confirmations</a>

#### Further information:

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5763-2UL36-0A../all>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VL5763-2UL36-0A..](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VL5763-2UL36-0A..)

##### CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Feb 8, 2013