## SIEMENS

## **Product data sheet**

## 5SM1344-6KK03



Similar to image

Technical data:					
mounting position		any			
Design of the product		Instantaneous			
Supply voltage / for AC / rated value	V	400			
Resistance against the impulse current / rated value	kA	1			
Ambient temperature	°C	-25 +45			
Ambient temperature					
during storage	°C	-40 +60			
Mechanical operating cycles as operating time / typical	_	10,000			
Overvoltage class		Ш			
Supply voltage / for testing equipment / minimum	V	100			
Protection against electrical shock		Finger and back-of-hand safe			
Position / of power supply cord		top or bottom			
Tightening torque					
with screw-type terminals	N∙m	2.5 3			
Section de conducteur raccordable					
• solid	mm²	1.5 25			
• multibrin	mm²	1.5 25			
Product feature					

RES.CURRENT OP.CIRCUIT BREAKER TYPE A PSE/SSF D=55MM 40A 3+N-POL IFN 30MA 400V 4MW 50-400HZ

• [not supplied - silicon-free]				Yes			
<ul> <li>halogen-free</li> </ul>				Yes			
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30			28				
Certificates/approvals:							
General Product Approval	Declaration of Conformity	Test Certificates			other		
PG	CE	Special Test Certificate	Type Test Certificates/Te	est	Environmental Confirmations		

Report

Further	information:	

GOST

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

C

EG-Konf.

Industry Mall (Online ordering system)

http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/5SM1344-6KK03/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=5SM1344-6KK03

## CAx-Online-Generator

http://www.siemens.com/cax

Tender specifications
Datanorm GAEB81 GAEB83 RTF TXT

last change:

Dec 31, 2012