



RES.CURRENT OP.CIRCUIT BREAKER TYPE AC WS
D=55MM 80A 3+N-POL IFN 30MA 400V 4MW

Similar to image

Technical data:

mounting position		any
Design of the product		Instantaneous
Supply voltage / for AC / rated value	V	400
Resistance against the impulse current / rated value	kA	1
Ambient temperature	°C	-5 ... +45
Ambient temperature • during storage	°C	-40 ... +60
Mechanical operating cycles as operating time / typical		10,000
Overvoltage class		III
Supply voltage / for testing equipment / minimum	V	100
Protection against electrical shock		Finger and back-of-hand safe
Position / of power supply cord		top or bottom
Tightening torque • with screw-type terminals	N·m	2.5 ... 3
Section de conducteur raccordable • solid	mm ²	1.5 ... 25
• multibrin	mm ²	1.5 ... 25
Product feature		

• [not supplied - silicon-free]	Yes
• halogen-free	Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30	28

Certificates/approvals:

General Product Approval	Declaration of Conformity
 CCC  GOST other	 VDE  ÖVE  EG-Konf.

Test Certificates	other
Special Test Certificate Type Test Certificates/Test Report	Environmental Confirmations

Further information:

- Information- and Downloadcenter (Catalogs, Brochures,...)**
<http://www.siemens.com/lowvoltage/catalogs>

- Industry Mall (Online ordering system)**
<http://www.siemens.com/lowvoltage/mall>

- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**
<http://support.automation.siemens.com/WWW/view/en/5SM1347-0/all>

- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM1347-0

- CAX-Online-Generator**
<http://www.siemens.com/cax>

last change: Dec 31, 2012