SIEMENS

Product data sheet

5SM1642-6



RES.CURRENT OP.CIRCUIT BREAKER TYPE A PSE/SSF D=55MM 25A 3+N-POL IFN 0,3A 400V 4MW

Similar to image

Technical data:						
mounting position		any				
Design of the product		Instantaneous				
Supply voltage / for AC / rated value	V	400				
Resistance against the impulse current / rated value	kA	1				
Ambient temperature	°C	-25 +45				
Ambient temperature						
during storage	°C	-40 +60				
Mechanical operating cycles as operating time / typical		10,000				
Overvoltage class		ш				
Supply voltage / for testing equipment / minimum	V	100				
Protection against electrical shock		Finger and back-of-hand safe				
Position / of power supply cord		top or bottom				
Tightening torque						
with screw-type terminals	N∙m	2.5 3				
Section de conducteur raccordable						
• solid	mm²	1.5 25				
• multibrin	mm²	1.5 25				
Product feature						

 [not supplied - sili 	icon-free]			Yes			
 halogen-free 				Yes			
Number of test cycle accordance with IEC	es / for environmental t C 60068-2-30	esting / in		28			
Certificates/appro	vals:						
General Product A	pproval					Declaration of Conformity	
GOST	KEMA	other		ö	VE	EG-Konf.	
Test Certificates		other					
Special Test Certificate	<u>Type Test</u> Certificates/Test Report	Environmental Confirmations					
Further information:							
Information- and Downloadcenter (Catalogs, Brochures,) http://www.siemens.com/lowvoltage/catalogs							
Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall							
Service&Support (Manuals, Certificates, Characteristics, FAQs,) http://support.automation.siemens.com/WW/view/en/5SM1642-6/all							
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams,) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SM1642-6							
CAx-Online-Generator http://www.siemens.com/cax							
Tender specification							

last change:

Dec 31, 2012