SIEMENS

Product data sheet



RES.CURRENT OP.CIRCUIT BREAKER TYPE AC WS D=55MM 63A 3+N-POL IFN 0,5A 400V 4MW

Similar to image

Technical data:					
mounting position		any			
Design of the product		Instantaneous			
Supply voltage / for AC / rated value	V	400			
Resistance against the impulse current / rated value	kA	1			
Ambient temperature	°C	-5 +45			
Ambient temperature					
during storage	°C	-40 +60			
Mechanical operating cycles as operating time / typical		10,000			
Overvoltage class		ш			
Supply voltage / for testing equipment / minimum	V	100			
Protection against electrical shock		Finger and back-of-hand safe			
Position / of power supply cord		top or bottom			
Tightening torque					
with screw-type terminals	N∙m	2.5 3			
Section de conducteur raccordable					
• solid	mm²	1.5 25			
• multibrin	mm²	1.5 25			
Product feature					

 [not supplied - s 	silicon-free]			Yes		
• halogen-free			Yes			
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30				28		
Certificates/appr	rovals:					
General Product Approval				Declaration of Conformity		
GOST	other		ÖVE	EG-Konf.		
Test Certificates		other				
Special Test Certificate	Type Test Certificates/Test Report	Environmental Confirmations				
Further informat	ion:					
	Downloadcenter (Catalog .com/lowvoltage/catalogs	s, Brochures,)				
	ne ordering system) .com/lowvoltage/mall					
	Manuals, Certificates, C					
•	roduct images, 2D dime ion.siemens.com/bilddb/ca	•	•	rcuit diagrams,)		
CAx-Online-Genera	ator					

http://www.siemens.com/cax

last change:

Dec 31, 2012