



CIRCUIT BREAKER T55 230/400V, 6KA,
1-POLE, C, 20A

General technical data:

type of voltage		AC/DC
Mounting depth	mm	55
Current / for AC / rated value	A	20
Tripping characteristic class		C
Supply voltage / for AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	10
• acc. to EN 60898 / rated value	kA	6
Number of pitch units for width		1
Degree of pollution		3
Overvoltage class		3

Certificates/approvals:

General Product Approval**Declaration of
Conformity**

CSA



GOST



KETI



UL



VDE



EG-Konf.

Test Certificates[Special Test
Certificate](#)[Type Test
Certificates/Test
Report](#)**Shipping Approval**

LRS

other[other](#)[Environmental
Confirmations](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/lowvoltage/mall>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/5SX2120-7/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2120-7**CAX-Online-Generator**<http://www.siemens.com/cax>**last change:**

Sep 24, 2012