SIEMENS

Product data sheet

5TE8315



Similar to image

Technical data:		
Mounting depth	mm	70
Operating voltage / rated value	V	400
Operating current / rated value	А	32
type of voltage		AC
Number of poles		4
Breaking capacity current / rated value	kA	0.096
Resistance against short-circuit current	kA	10
Design of the switching function		Off switch
Number of pitch units for width		4
Number of NC contacts		0
Number of NO contacts		4
Number of change-over switches		0
Product component / Signal lamp		No
Product function / positive opening (acc. to DIN VDE 0113)		No

SWITCH 32A 4NO

Certificates/approvals:

General Product Approval





GOS



Declaration of

Conformity

other

Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system) http://www.siemens.com/lowvoltage/mall

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) http://support.automation.siemens.com/WW/view/en/5TE8315/all


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE8315

CAx-Online-Generator

http://www.siemens.com/cax

· ·

Tender specifications Datanorm GAEB81 GAEB83 RTF TXT



last change:

Nov 16, 2012