

# SIEMENS

## Product data sheet

## 6ED1052-2HB00-0BA6



LOGO! 24RC0 (AC), LOGIC MODULE,  
 PU/I/O: 24V UC/24V UC/RELAY, 8 DI/4 DO;  
 W/O DISPLAY, MEMORY 200 BLOCKS,  
 EXPANDABLE WITH EXTRA MODULES

Installation type/mounting	
Mounting	on 35 mm DIN rail, 4 spacing units wide
Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
24 V AC	Yes
Time of day	
Time switching clocks	
Number	8
Power reserve	80 h
Digital inputs	
Number/binary inputs	8
Digital outputs	
Number/binary outputs	4 ; Relay

Functionality/short-circuit strength	No ; external fusing necessary
<b>Relay outputs</b>	
<b>Switching capacity of contacts</b>	
with inductive load, max.	3 A
Switching frequency/contacts/at ohmic load/maximum	10 A
<b>EMC</b>	
<b>Emission of radio interference acc. to EN 55 011</b>	
Emission of radio interference acc. to EN 55 011 (limit class B)	Yes
<b>Degree and class of protection</b>	
IP20	Yes
<b>Standards, approvals, certificates</b>	
CSA approval	Yes
UL approval	Yes
FM approval	Yes
Marine approval	Yes
Developed according to IEC 61131	Yes
according to VDE 0631	Yes
<b>Ambient conditions</b>	
<b>Operating temperature</b>	
Min.	0 °C
max.	55 °C
<b>Dimensions</b>	
Width	72 mm
Height	90 mm
Depth	55 mm
Status	Jul 17, 2012