



COMMUNICATION PROCESSOR CP 5611 -MPI, CONSISTING OF PCI CARD CP 5611 A2 (32BIT; 3.3/5V; 33/66 MHZ) FOR CONNECTING PG/PC WITH PCI-BUS TO PROFIBUS OR MPI INCL. MPI CABLE, 5M 1X 6GK1561-1AA01 1X 6ES7901-0BF00-0AA0 (NO WIN9X-SUPPORT!) CURRENTLY ONLY 32BIT SUPPORT IN CONNECTION WITH SIMATIC NET V8.2 SW!

Transmission rate

Transmission rate

- at interface 1 / in accordance with PROFIBUS
 - minimum 9.6 kbit/s
 - maximum 12 Mbit/s

Interfaces

Number of electrical connections / at interface 1 / in accordance with PROFIBUS 1

Supply voltage, current consumption, power loss

Supply voltage

- 1 / from backplane bus 5 V

Relative symmetrical tolerance

- at 5 V / with DC 5 %

Consumed current

- 1 / from backplane bus / with DC / maximum 0.5 A

Resistive loss 2.5 W

Permitted ambient conditions

Ambient temperature

- during operating 5 ... 40 °C
- during storage -20 ... +60 °C
- during transport -20 ... +60 °C

Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP00
Design, dimensions and weight	
Width	18 mm
Height	102 mm
Depth	130 mm
Net weight	300 g
Product properties, functions, components / general	
Number of plug-in cards in the same design / can be plugged in / per PC station	1
Performance data	
Performance data / open communication	
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	50
Performance data / PROFIBUS DP	
Service / as DP master	
• DPV0	Yes
• DPV1	No
• DPV2	No
Number of DP slaves / on DP master / usable	64
Amount of data	
• of the address area of the inputs / as DP master / overall	14640 byte
• of the address area of the outputs / as DP master / overall	14640 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	244 byte
Service / as DP slave	
• DPV0	Yes
• DPV1	No
Amount of data	
• of the address area of the inputs / as DP slave / overall	122 byte
• of the address area of the outputs / as DP slave / overall	122 byte
Performance data / S7 communication	
Number of possible connections / for S7/PG communication / maximum	8
Performance data / multi-protocol mode	
Number of configurable connections / per PC station	207
Product functions / Diagnosis	
Product function / Port diagnostics	Yes
Standards, specifications, approvals	

Verification of suitability

- CE mark
- C-Tick

letzte Änderung:

Yes

Yes

Jul 17, 2012