



LOGO! CSM 12/24 COMPACT SWITCH MODULE
 CONNECT. TO LOGO! (..0BA7) AND UP TO 3 ADDITIONAL
 CLIENTS TO IND. ETHERNET W. 10/100 MBIT/S
 UNMANAGED SWITCH,
 4 RJ45 PORTS,
 1XFRONTPORT FOR DIAGNOSTICS 12/24V DC POWER
 SUPPLY LED DIAGNOSTICS,
 LOGO! CONFIG.

Transmission rate

Transfer rate / 1	10 Mbit/s
Transfer rate / 2	100 Mbit/s

Interfaces

Number of electrical/optical connections / for network components or terminal equipment / maximum	4
Number of electrical connections	
• for network components and terminal equipment	4
• for power supply	1
Design of electrical connection	
• for power supply	3-pole terminal block

Supply voltage, current consumption, power loss

Supply voltage / external	24 V
• minimum	10.2 V
• maximum	30.2 V
Product component / fusing at power supply input	Yes
Consumed current / maximum	0.15 A
Active power loss / at 24 V / for DC	1.5 W

Permitted ambient conditions

Ambient temperature	
• during operating	0 ... 55 °C

• during storage	-40 ... +70 °C
• during transport	-40 °C
Relative humidity	
• at 25 °C / without condensation / during operating / maximum	90 %
Protection class IP	IP20

Design, dimensions and weight

Width	72 mm
Height	90 mm
Depth	55 mm
Net weight	0.14 kg
Type of mounting	
• 35 mm DIN rail mounting	Yes
• wall mounting	Yes
• S7-300 rail mounting	No

Product properties, functions, components / general

Product function / switch-managed	No
Standard	
Verification of suitability	
• CE mark	Yes
• C-Tick	Yes
• KC approval	No

letzte Änderung: Jul 20, 2012